



## Filter Model Number Selection



### How to Build a Valid Model Number for a Schroeder WQLF15:



**Example:** NOTE: One option per box



BOX 1	BOX 2	BOX 3	BOX 4
<b>Filter Series</b>	<b>Number of Elements</b>	<b>Element Size and Media</b>	<b>Housing Seal Material</b>
WKL3	1 2 3	KM10 = 10 μ M media (reusable metal) KM25 = 25 μ M media (reusable metal) KM60 = 60 μ M media (reusable metal) KM150 = 150 μ M media (reusable metal) KM260 = 260 μ M media (reusable metal)	Omit = Buna N H = EPR V = Viton®

BOX 5	BOX 6
<b>Porting</b>	<b>Dirt Alarm® Options</b>
P24 = 1½" NPTF S24 = SAE-24 F24 = 1½" SAE 4-bolt flange Code 61 B24 = ISO 228 G-1½" P32 = 2" NPTF S32 = SAE-32 B32 = ISO 228 G-2"	Omit = None Visual D5 = Visual pop-up <b>D9 = All stainless D5 (Recommended)</b> <b>D9C = D9 in cap (Recommended)</b> Electrical MS5SS = All stainless MS5 Electrical w/ 12 in. 18 gauge 4-conductor cable MS10SS = All stainless MS10 Electrical w/ DIN connector (male end only) Electrical Visual MS13SS = All stainless MS13 Supplied w/ threaded connector & light

BOX 7	BOX 8
<b>Test Port Options</b>	<b>Bowl Drain Options</b>
Omit = None L = Two ¼" NPTF inlet and outlet female test ports	Omit = None DR = 7/16" -20 drain on bottom of housing

#### NOTES:

Box 4. Replacement element part numbers are a combination of Boxes 2 and 3, and the letter V.  
Example: KM10V

Box 5. All elements for this filter are supplied with Viton® seals. Seal designation in Box 4 applies to housing only. Viton® is a registered trademark of DuPont Dow Elastomers.

Box 6. D9/D9C indicator is the recommended option.

Contact factory for more Dirt Alarm® options