

Multi-Gauge



P/N GS-5



P/N GS-6U

The Schroeder Multi-Gauge provides multiple pressure readings for hydraulic, transmission, and converter systems all in one handy, compact enclosure. While one hook-up connects all three gauges, the built-in gauge protector automatically protects the low and medium pressure gauges from high pressures. Each gauge is equipped with a high quality poppet valve. The Multi-Gauge is available with two types of connections: (1) the standard braided copper, flexible high pressure hose with male 1/8" pipe universal swivel fitting and (2) microbore flexhose and test point adapter (specified by U in the part number).

- **Protects against overpressurization.** The 150 psi gauge can not be damaged when a 2500 psi system is being checked. This design feature eliminates the need to know the pressure before testing.
- **Simple yet rugged construction.** The dust and moisture proof steel case is provided with a rubber bumper for shock protection. A hanger is also provided on the case back for the user's convenience.
- **Compact and portable.** The GS-5 and GS-6 models are 6-1/2" and 8-1/2" in diameter. The GS-5 fits easily into the average tool box for instant availability.
- **Saves time.** The three pressure ranges and one vacuum range provided in one case meet most routine hydraulic maintenance requirements.

	GS-5 & GS-5U	GS-6 & GS-6U
Case Diameter:	6.31 in (160 mm) O.D.	8.50 in (216 mm) O.D.
Gauge Diameter:	1.50 in (38 mm) O.D.	1.50 in (38 mm) O.D.
Approximate Weight:	3.25 lbs (1.47 kg)	4.5 lbs (2.0 kg)
Range:	Vacuum (30" Hg) to 5000 psi (345 bar)	Vacuum (30" Hg) to 6000 psi (3413 bar)
Case:	Steel with rubber bumper strip	Steel with rubber bumper strip
Vacuum Gauge:	30 in Hg	30 in Hg
Pressure Gauges:	0 to 150 psi (10 bar) 0 to 600 psi (41 bar) 0 to 5000 psi (345 bar)	0 to 300 psi (21 bar) 0 to 1000 psi (69 bar) 0 to 6000 psi (414 bar)

How to Build a Valid Model Number for a Schroeder GS:

BOX 1	BOX 2
GS	

Example: NOTE: One option per box

BOX 1	BOX 2
GS	5U

BOX 1	BOX 2
Model Number	Options
GS	5 Standard Multi-Gauge 5U Multi-Gauge with Microbore Flexhose and Test Point Adapter 6 Multi-Gauge with 2-1/2" Liquid Filled Gauges 6U Multi-Gauge with 2-1/2" Liquid Filled Gauges, Microbore Flexhose and Test Point Adapter

GS Multi-Gauge

- TCM
- TCM-FC
- TSU
- TMU
- TPM
- TIM
- TMS
- CTU
- TWS-C
- ET-100-6
- HMG 3000
- EPK

Description

HTB
GS

Trouble Check Plus

Test Points

Features

Adapters

Hose Joiners

Microflex Hose

Pressure Limiters

Pressure Gauges

Test Kits

Probalizer

Filtration Station

MFS, MFD

AMS, AMD

KLS, KLD

AKS, AKD

KLC

X Series

MTS

HFS

SVD

TDS-A

TDS-E

IXU

Appendix