

# BestFit<sup>®</sup> for Donaldson Duramax<sup>®</sup>\*

Schroeder Industries is pleased to announce the release of the NEW BestFit element series equivalent in form, fit and function to the Donaldson Duramax<sup>®</sup> line.

The BestFits are available with either fiberglass or cellulose media, for use in a wide range of applications. As always, these elements are priced competitively to capture the aftermarket business. Information follows regarding conversions, dimensions, and technical details.

## HMK 05 Series

Donaldson P/N	Schroeder BestFit P/N
P165569	SBF16556911Z25
P165659	SBF16565911Z25

## HMK 04 Series

Donaldson P/N	Schroeder BestFit P/N
P163324	SBF1633249E25
P163425	SBF1633249E25
P163405	SBF1634056E25
P163428	SBF1634056E25
P163496	SBF1634056E25
P164375	SBF1643756Z25
P164378	SBF1643789Z10
P164381	SBF1643816Z10
P164384	SBF1643849Z10
P165332	SBF1653329Z5

## Technical Details

### Temperature Range

Cellulose (E Media):	-20° to 225°F (-29° to 107°C)
Excellement (Z Media):	-20° to 250°F (-29° to 121°C)

### Element Pressure Rating

	4 inch	5 inch
Min. Collapse Rating:	150 psi	200 psi
Max. Pressue Rating:	500 psi	350 psi
Burst Pressure:	1000 psi	800 psi



## Dimensions

Schroeder BestFit Number	OD (inches)	Length (inches)
SBF1633249E25	3.75	9.5
SBF1634056E25	3.75	6.0
SBF1643756Z25	3.75	6.0
SBF1643789Z10	3.75	9.5
SBF1643816Z10	3.75	6.0
SBF1643849Z10	3.75	9.5
SBF1653329Z5	3.75	9.5
SBF16556911Z25	4.75	11.5
SBF16565911Z25	4.75	11.5

\*Duramax is a registered trademark of Donaldson.

**Schroeder**  
INDUSTRIES

580 West Park Road • Leetsdale, PA 15056  
p. 724.318.1100 • f. 724.318.1200